

#### ICBCL4250SID/S



#### **FEATURES**

ClearSight™ LED lighting system fully illuminates the interior and reduces shadows

Split Climate™ intelligent cooling system revolutionises Sub-Zero's already-superior preservation capabilities, keeping food even fresher for longer

Night Mode optimizes the interior lighting based on the detected ambient light, reducing the brightness by 90% in dim environments

Touch control panel is conveniently located for easy access at the tap of a finger

Sleek stainless accents trim the interior, matching the sophistication of the exterior

Stainless-steel exterior and tubular or pro handles to match other Sub-Zero and Wolf products

Delivers fresh-tasting, filtered water through an internal dispenser located discreetly within the refrigerator

Lift the base of the flip-up dairy compartment to store taller items on the shelf below

Activate Max Ice Mode to temporarily increase ice production

Sub-Zero offers an industry-leading full two-year warranty on appliances, along with a full five-year sealed system warranty

#### **ACCESSORIES**

Air Purification Cartridge

Egg Container

Stainless Steel Pro Louvered Grille - 84"

Grilles for 83" or 88" finished height (84" is standard)

Stainless Steel Kickplate

Accessories are available through an authorized dealer. For local dealer information, visit <a href="mailto:subzero-wolf.com/locator">subzero-wolf.com/locator</a>.



#### **HANDLE OPTIONS**



# **PRODUCT DETAILS**

## REFRIGERATOR

- 5 glass refrigerator shelves (4 adjustable; 1 stationary)
- · 4 crisper drawers with removable dividers
- 5 refrigerator door bins (3 adjustable; 2 stationary)
- 1 flip-up dairy compartment
- Air purification system
- · Internal ice and water dispenser
- · LED refrigerator and freezer lights

# **FREEZER**

- 5 adjustable door bins
- · 3 storage drawers
- · Fold-up shelf
- · Water filtration system




#### **PRODUCT SPECIFICATIONS**

Model	ICBCL4250SID/S
Dimensions	1067mmW x 2134mmH x 610mmD
Refrigerator Capacity	485 L
Freezer Capacity	272 L
Weight	283 kg
Electrical Supply	220-240 VAC; 50/60 Hz
Electrical Service	≤ 4 A
Receptacle	3-prong grounding-type

PANEL SPECIFICATIONS For complete panels specifications including width/height, weight requirements, thickness requirements and offset details visit <a href="mailto:subzero-wolf.com/builtinconfigurator">subzero-wolf.com/builtinconfigurator</a>.

NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

#### **INTERIOR VIEW**



This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

# **DIMENSIONS**

